

US006404701B1

(12) United States Patent Stottlemyer

(10) **Patent No.:**

US 6,404,701 B1

(45) **Date of Patent:**

Jun. 11, 2002

(54) ENCAPSULATED VOLUMETRIC ACOUSTIC ARRAY IN THE SHAPE OF A TOWED BODY

5) Inventor: Thomas R. Stottlemyer, Mystic, CT

(US)

(73) Assignee: The United States of America as

represented by the Secretary of the Navy, Washington, DC (US)

(*) Notice:

(56)

Subject to any disclaimer, the term of this patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

(21) Appl. No.: 09/906,007

(22) Filed: Jul. 16, 2001

(51) Int. Cl.⁷ H04R 17/00

367/106, 130; 174/101.5

References Cited

U.S. PATENT DOCUMENTS

3,900,543 A	*	8/1975	Davis 174/101.5
4,733,379 A	*	3/1988	Lapetina et al 367/20
			Jackett et al 367/155

5,241,519 A	*	8/1993	Monahan et al 367/154
5,412,621 A	*	5/1995	Hepp 367/154
5 777 954 A	*	7/1998	Hepp 367/20

* cited by examiner

Primary Examiner—Ian J. Lobo (74) Attorney, Agent, or Firm—Michael J. McGowan; Prithvi C. Lall; Michael F. Oglo

(57) ABSTRACT

An encapsulation assembly includes a housing having a nose end, a tail end, and a body portion between the nose end and the tail end. A plurality of acoustic transducers are positioned within the body portion of the housing, each of the plurality of acoustic transducers having a wiring connection attached thereto. A tow cable is connected to the nose end of the housing and is in communication with the wiring connection from each of the plurality of acoustic transducers. A characteristic of the assembly is that at least the body portion of the housing is entirely formed of a solid casting of plastic material thereby environmentally isolating the plurality of acoustic transducers within the body portion of the housing. This configuration prevents water intrusion into the transducer elements, and increases the cavitation threshold for the acoustic array, thereby allowing the array to be driven to higher acoustic intensities.

7 Claims, 1 Drawing Sheet

